



Auswerferstifte mit zylindrischem Kopf

nach DIN 1530 Teil 1, Form A, badnitriert (schwarz)
und blanknitriert, ähnlich ISO 6751

d ₁ g6	d ₂	Grenzabmaße	d ₃	k +0,2 0	r	l ₁ +2 0						l ₂
						100	125	160	200	250	315	
0,8	1,4		0,92			●	●	●	●	●		
0,9	1,6		1,01			●	●	●	●	●		
1,0			1,19			●	●	●	●	●		
1,1		1,8	1,11			●	●	●	●	●		
1,2			1,19			●	●	●	●	●		
(1,25)		2,0	1,15			●	●	●	●	●		
1,3			1,11			●	●	●	●	●		
1,4		2,2	1,19			●	●	●	●	●		
1,5			1,11			●	●	●	●	●		
1,6			1,28			●	●	●	●	●		
1,7		2,5	1,19			●	●	●	●	●		
(1,75)			1,15			●	●	●	●	●		
1,8		2,8	1,37			●	●	●	●	●		
1,9			1,28	+0,3	0,4 0	●	●	●	●	●		
2,0	3,0		1,37	+0,03		●	●	●	●	●	●	5
2,1			1,45			●	●	●	●	●		
2,2		3,2	1,37			●	●	●	●	●		
(2,25)			1,32			●	●	●	●	●		
2,3			1,54			●	●	●	●	●		
2,4		3,5	1,45			●	●	●	●	●		
2,5			1,37			●	●	●	●	●		
2,6		0,1 +I	1,71			●	●	●	●	●		
2,7		4,0	1,63			●	●	●	●	●		
(2,75)			1,58			●	●	●	●	●		
2,8			1,54			●	●	●	●	●		
2,9			1,45			●	●	●	●	●		
3,0		4,5	1,80	+0,4	0,6 0	●	●	●	●	●	●	14
3,1			1,71			●	●	●	●	●		

d ₁ g6	d ₂	Grenzabmaße	d ₃	k +0,2 0	r	l ₁ +2 0						l ₂
						100	125	160	200	250	315	
3,2			4,5			●	●	●	●	●		
(3,25)						●	●	●	●	●		
3,5			5,0			●	●	●	●	●		
(3,75)						●	●	●	●	●		
4,0			5,5			●	●	●	●	●	●	5
4,1						●	●	●	●	●		
4,2			(4,25)			●	●	●	●	●		
4,5			6,0			●	●	●	●	●		
5,0						●	●	●	●	●		
5,1			6,5			●	●	●	●	●		
5,2			(5,25)			●	●	●	●	●		
5,5			7,0			●	●	●	●	●		
6,0			8,0			●	●	●	●	●		6
6,2						●	●	●	●	●		
6,5			9,0			●	●	●	●	●		
7,0						●	●	●	●	●		
7,5			10,0	+0,2	+I	●	●	●	●	●		
8,0						●	●	●	●	●		
8,2						●	●	●	●	●		
8,5			11,0			●	●	●	●	●		
9,0						●	●	●	●	●		
10,0			12,0			●	●	●	●	●	●	10
11,0			13,0			●	●	●	●	●		
12,0			14,0			●	●	●	●	●		12
14,0			16,0			●	●	●	●	●		14
16,0			18,0			●	●	●	●	●		16

● = ab Lager lieferbar.